

ProJet™ 1500

Personal Color 3D Printer

The new ProJet™ 1500 Personal Color 3D Printer combines high resolution, color and fast speed at an affordable price.

- High Resolution
- Vibrant Colors
- Durable Parts



Finally, A 3D Printer for the Rest of Us!

The ProJet™ 1500 has a sleek industrial design to complement your office or work space. It's easy to use and network ready, featuring an intuitive web browser interface that provides shared access for your entire group.



The ProJet™ 1500 prints durable plastic parts tough enough for functional testing and snap-fit applications in up to 6 different colors with excellent high resolution detail and smooth surface finish.

Bring your designs to life at print speeds up to 5 times faster than any other 3D printer in its class.



ProJet™ 1500

Personal 3D Printer



PRINTER PERFORMANCE	
Max Build Size (XYZ)	6.75 x 9 x 8 in (171 x 228 x 203 mm)
Native Resolution (xy)	1024 x 768 DPI
Layer Thickness	Standard Mode 0.004 in (102 μm) High speed Mode 0.006 in (152 μm)
Vertical Build Speed	Standard Mode 0.5 in/hour High speed Mode 0.8 in/hour (VisiJet® FTI-Zoom material only)
Min Feature Size	0.010 in (0.254 mm)
Min Vertical Wall Thickness	0.025 in (0.64 mm)
PRINTER SPECIFICATIONS	
File Types Supported	stl, ctl
Dimensions (W x D x H)	Uncrated 21.8 x 36 x 28.5 in (555 x 914 x 724 mm) Crated 24.5 x 39.5 x 30.5 in (622 x 1003 x 775 mm)
Weight	Uncrated 122 lbs (55.3kg) Crated 150 lbs (68 kg)
Power Requirement	100-120 VAC 50/60 Hz, 3A; 220-240 VAC 50/60 Hz, 1.5A
Ambient Noise	Under 60 dBA (measured 1m from the printer)
File Types Supported	STL, CTL
Network Compatibility	RJ45 - 10/100
Workstation Requirement	Windows® XP, Windows® Vista, Windows® 7 running Internet Explorer 8 or higher, Firefox 5 or higher, or Chrome 12 or higher
Regulatory Compliance	CE, RoHS, WEEE

MATERIALS	ASTM	UNITS	IVORY ○	RED ●	GREY ●	BLUE ●	BLACK ●	ZOOM ●
Cartridge Quantity		kg	2	2	2	2	2	2
Density (liquid) @ 30 °C		g/cm³	1.08	1.08	1.08	1.08	1.08	1.08
Tensile Strength	D 638	MPa	12 - 22	8 - 18	8 - 18	10 - 24	13 - 25	15 - 29
Tensile Modulus	D 638	MPa	800 - 1200	400 - 600	600 - 1000	600 - 1300	600 - 1000	800 - 1500
Elongation at Break	D 638	%	2 - 3	2 - 4	2 - 3	2 - 3	2 - 4	2 - 3
Flexural Strength	D 790	MPa	23 - 34	16 - 22	20 - 36	13 - 29	19 - 34	29 - 53
Flexural Modulus	D 790	MPa	750 - 1100	500 - 700	700 - 1000	300 - 800	600 - 1000	900 - 1400
Impact Strength	D 256	J/m	16	17	17	16	17	19
Heat Deflection Temperature	D 648	°C	52	50	45	47	50	52
Hardness, Shore D			77 - 80	65 - 70	75 - 80	70 - 80	75 - 82	72 - 85
Glass Transition, T _g	DMA, E''	°C	82	77	80	74	84	82

The VisiJet FTI-Zoom material also builds up to 40% faster in high speed mode.



EmberSurge
1017 El Camino Real
Redwood City, CA 94063
Telephone 650.533.0011
contact@embersurge.com

Warranty/Disclaimer: The performance characteristics of these products may vary according to product application, operating conditions, material combined with, or with end use. 3D Systems makes no warranties of any type, express or implied, including, but not limited to, the warranties of merchantability or fitness for a particular use.

© 2011 by 3D Systems, Inc. All rights reserved. Specifications subject to change without notice. The 3D Systems logo and stylized text are trademarks and 3D Systems and V-Flash are registered trademarks of 3D Systems, Inc.

PN 70753 Issue Date September 2011

www.embersurge.com